



ADE4304S

5MP 5 IN 1 4CH Stand Alone DVR

Features

- ◆ ONVIF IP camera comparable
- ◆ Support Analog AHD / TVI / CVI 5MP(5MN), IP 5MP switchable
- ◆ Supports multiple web browsers
- ◆ Build in IP PTZ control function
- ◆ Build in UTC control function
- ◆ Build-in VGA / HD Output
- ◆ Remote Configuration
- ◆ Build in surge protector
- ◆ P2P Mobile APP Supported
- ◆ Dual Video Streaming
- ◆ 2 ways audio capabilities.
- ◆ Can build in 1 internal SATA HDD up to 10TB
- ◆ Remote access through mobile phone .
- ◆ GUI (mouse) operation
- ◆ Support AI Alarm such as Face / Human / IVS

Specification

System	O.S.	Embedded Linux
	Operation	Multiplex - simultaneous record, live, playback, setup, backup, control, and remote access
Video	Format	IP-CAM: ONVIF Profile S, Profile T Analog: NTSC or PAL, AHD or TVI or CVI, CVBS
	Input	IP-CAM: up to 4CH 5MP ; Analog: up to 4CH , AHD/TVI/CVI: 5MN or 960H, BNC, 1Vp-p/75ohm
	Main monitor	HD x 1, with resolution up to 1920x1080, VGA x 1, with resolution up to 1920x1080
	Mode	HD / IP / HD+IP
	Alarm detection	Motion / Video loss / Video blind / Face Detection / Human Detection / IVS (IP channel)
	Detection Settings	Channel / Region / Time / Sensitivity
Audio	Input	1 RCA-jack connectors, 4CH coaxial audio support
	Output	1 HD, 1 RCA-jack connector
Record	Compression	Audio: ADPCM
	Max frame rate & resolution	MainStream: 4CH 5MN@12fps / 2MP@15fps (IP 4CH-5MP@30fps) ; SubStream: D1@7fps / CIF@28fps
	Mode	Manual / Schedule / Alarm / Detection
	Pre-record time	Yes
	Post-record time	Yes
	Redundant record	Yes
Display	Resolution	HD & VGA, up to 1920x1080
	Frame rate	Up to 30/25fps per display window
	Digital Zoom	Yes
	Sequential switch	User adjustable
Playback	Max frame rate & resolution	HD: 4 ch 5MN 12fps (IP: 1ch 5MP@30fps) ; HD+IP:1 ch 5MN/5MP
	Search	Date/time, Camera, Alarm, Detection
Storage	HDD	1 set of SATA HDD with storage < 8TB
	HDD Property	Read/Write, Read only, Redundant, Snapshot
	Backup	2 USB 2.0 port, Backup files support avi format

Alarm	Buzzer	Yes
	Triggered by	HDD Failure / Net Disconnection / IP Conflict / Motion / Video loss / Video blind / Face Detection / Human Detection / IVS (IP only)
	External I/O	N/A
	Face Detection	Analog channel: CH1
Human / Vehicle Detection	Human / Vehicle Detection	Analog channel: CH1 (Human Detection) IP channel: supports AuViss IP cameras only, depending on camera function
	IVS	Line crossing / Area intrusion (IP channel only) IP channel: supports AuViss IP cameras only, depending on camera function
Network	Ethernet	1 RJ-45 100M Ethernet
	Web	Support Windows 11/10/8/7, I.E / Chrome/ Edge
	E-mail/Push alarm	Alarm notification to mobile devices
	Video	Live viewing, Playback, Settings
	Audio	Bidirectional simplex voice
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, NTP, RTSP, P2P
	Remote users	Up to 6 users simultaneously
	DDNS dynamic domain service	Free DDNS
	Remote stations	Support PC, mobile phone, and tablet connection, Free iOS/Android Mobile APP.
	Control	RS-485
Setup	Local	Graphical UI user interface; Mouse operation
	Multi-lingual	Yes
Reliability	System recovery	Auto power on after power loss recovery
	Timer	Supports NTP for time synchronisation
Weights & Measures	Security	Multi-level password
	Dimension	255(W) x 235(D) x 45(H)mm
Power	Weight	1.24 KG (without HDD)
	Source	DC 12V
	Consumption	18W Max. (with HDD)
Operating Temperature		0°C ~ +50°C