



AHP2515T-F3-YR20

2MP Mini smart dual-light Wireless Bullet IP Camera

Features

- ◆ 2MP, 1/2.8" CMOS sensor
- ◆ H.264/H.265 video compression
- ◆ Maximum resolution of 2592x1944 @ 20fps
- ◆ Dual encoding streams supported
- ◆ 3.6mm HD fixed lens, ICR filter
- ◆ Intelligent dual-light full-color + infrared, 10-20 meters effective IR distance
- ◆ Support IOS/Android Mobile view and control
- ◆ Support IE, Edge, Chrome, Firefox & Safari
- ◆ Build-in microphone and waterproof speaker
- ◆ IP66 weatherproof
- ◆ Metal casing and gimbal bracket
- ◆ 2.4GHz WIFI/5dBi antenna
- ◆ Support DC12V power supply
- ◆ Support VMS remote management system
- ◆ Built-in MicroSD card slot (supports simultaneous recording of MicroSD and NVR)

Specification

Camera		Network	
Image Sensor	1/2.8" CMOS	Remote Viewer	IOS/Android APP, IE, Edge, Chrome, Firefox & Safari, CMS software
Operating System	Embedded Linux	Alarm Trigger	Motion Detection/ Video loss/ Video Tampering/ Around Alarm/ Human Detection/ Sound Detection/ Alarm Input
Min. Illumination	Color: 0.1Lux(F1.2, AGC OFF) B/W: 0.01Lux(F1.2, AGC OFF); 0 Lux with IR	Protocols	TCP/IP, RTP, RTSP, HTTP, DNS, DDNS, DHCP, FTP, NTP, UPNP
Shutter Time	1/25 ~ 1/100000s	User Management	Max 8 Users
Lens	3.6mm 3MP fixed lens	Cloud	Build in cloud ID
SNR	≥ 45dB(AGC OFF)	System Compatibility	ONVIF (Profile S / T), SDK
Day& Night	Auto / Color / B/W	Connection Interface	
Wide Dynamic Range	DWDR	Internet	1-ch RJ45 10M / 100M Ethernet
Compression Standard		Wireless	IEEE 802.11b/g/n, 2.4GHz
Video Compression	H.264/H.265	External Alarm I/O	1/1
Video Bit Rate	175Kbps~5851Kbps	Internal Speaker	Yes
Audio Compression	G.711A (build internal microphone)	Internal Microphone	Yes
Audio Bit Rate	8~64Kbps	Internal MicroSD Slot	Yes
Image		General	
Max. Image Resolution	2592x1944 (5MP)	Language	English, Traditional Chinese
Main Stream	Max 20fps@2952x1944, 20fps@ 2560x1440, 20fps@ 1920x1080	Operating Conditions	-0°C~ 50°C, 0 ~ 95% RHG
Sub-Stream	Max 20fps VGA (640x480), 20fps CIF (352x288)	Power Supply	DC 12V ± 10%
Image Settings	Brightness, Saturation, Contrast, Tone, Sharpness, Flip Mode Adjustable, D/N image configuration	Power Consumption	DC 12V / 8W (Max.)
Image Processing	D/N mode management, DNR, Backlight compensation, Anti-Flicker, AE setup	Weather Proof	IP66
OSD	Week, Date, Time and Channel name	IR Range	10m~20m
Privacy Mask	N/A	IR LEDs	4pcs dual light LED
		Image Mode	Support Color to B/W, AI (switch to color mode while human triggered) and full color mode. Default in B/W mode
		Dimensions	177mm×63mm×65mm
		Weight	360g